

ZONES MULTIPLES

**SEER 22-21**

18 000 BTU À 56 000 BTU

MULTI ZONE

**22-21 SEER**

18,000 BTU TO 56,000 BTU

ZONES MULTIPLES

MULTI ZONE



WABBA



APPAREIL EXTÉRIEUR / OUTDOOR UNIT		BBM18H4-O	BBM24H4-O	BBM30H4-O	BBM36H4-O	BBM42H3-O
Nombre de ports / Number of ports		2 ports	3 ports	4 ports	5 ports	5 ports
Capacité / Capacity	Refroidissement / Cooling	BTU/h (6,998 - 21,000)	24,000 (7,500 - 33,000)	28,400 (8,188 - 33,438)	34,000 (8,871 - 35,826)	39,000 (8,871 - 40,944)
	Chauffage / Heating	BTU/h (7,000 - 22,600)	26,000 (7,500 - 27,978)	30,000 (8,189 - 32,414)	42,500 (8,871 - 44,356)	45,000 (8,871 - 46,062)
SEER		22	21	21	21	21
HSPF / COP		10.5 / 3.66	10.5 / 3.72	10.5 / 3.74	10.5 / 3.70	10.2 / 3.61
Alimentation / Power Supply		208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph
Débit d'air / Airflow		PCM CFM	1,883	2,354	2,354	4,531
Plage de fonctionnement / Operating Range	Refroidissement / Cooling	°C	-18 ~ 48	-18 ~ 48	-18 ~ 48	-18 ~ 48
		°F	0 ~ 118	0 ~ 118	0 ~ 118	0 ~ 118
	Chauffage / Heating	°C	-20 ~ 24	-20 ~ 24	-20 ~ 30	-20 ~ 30
		°F	-5 ~ 75	-5 ~ 75	-5 ~ 86	-5 ~ 86
Niveau de pression acoustique / Sound Pressure Level		dB(A)	56	58	59	61
Raccord de tuyauterie / Piping Connection	Liquide / Liquid	po. / in.	2 x 1/4	3 x 1/4	4 x 1/4	5 x 1/4
	Gaz / Gas	po. / in.	2 x 3/8	3 x 3/8	4 x 3/8	5 x 3/8
Dimensions (L x H x P) / Dimensions (W x H x D)		po. / in.	37.6 x 27.5 x 15.6	38.6 x 31.1 x 16.8	38.6 x 31.1 x 16.8	42.8 x 43.4 x 17.3
Poids net/brut / Net/Gross Weight		lb	114.4 / 125	152.9 / 164.2	154.0 / 169	198.0 / 216
Tuyauterie total max. / Max. Total Piping		pi. / ft.	65.6	196.8	229.6	246.0
Distance unique max. / Max. Single Distance		pi. / ft.	49	65.6	82.0	82.0
Élévation maximale / Max. Elevation		pi. / ft.	49	49	49.2	49.2
Charge de réfrigérant / Refrigerant Charge		lb	3.5	4.8	6.2	8.0
MOCP		A	25	30	30	35

1 WABBA

+ MARQUE QUÉBÉCOISE